

11555 Medlock Bridge Road, Suite 100, Johns Creek, GA 30097, USA

T: +1.888.658.1221 F: 1.678.619.2020

E: info@ereztech.com W: https://ereztech.com

SAFETY DATA SHEET

Section 1. Identification

Product Name: <u>Tetrakis(diethylamino)hafnium</u>

Product Type: Liquid

CAS Number: 19824-55-6 Product Number: HF4556

Recommended Use: Laboratory chemicals, synthesis of substances.

Uses Advised Against: This product is being supplied under the TSCA R&D Exemption (40

CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless

appropriate consent is granted in writing by Ereztech LLC.

Product Manufacturer: Ereztech LLC

11555 Medlock Bridge Road, Suite 100

Johns Creek, GA 30097

Product Information: (888) 658-1221

In Case of an Emergency: CHEMTREC: 1-800-424-9300 (USA);

+1 703-527-3887 (International); CCN836180
*** Contact manufacturer for all non-emergency calls.

Section 2. Hazards Identification

Appearance/Odor: Light yellow liquid, odor not determined.

Classification: FLAMMABLE LIQUIDS – Category 2, H225

SUBSTANCE AND MIXTURES, WHICH IN CONTACT WITH WATER,

EMIT FLAMMABLE GASES – Category 2, H261

SKIN CORROSION/IRRITATION – Category 2, H315

SERIOUS EYE DAMAGE/EYE IRRITATION – Category 2, H319 SPECIFIC ORGAN TOXICITY, SINGLE EXPOSURE; RESPIRATORY

TRACT IRRITATION – Category 3, H335

GHS Label Elements
Hazard Pictograms:





Section 2. Hazards Identification

Signal Word: DANGER

Hazard Statements: H225: Highly flammable liquid and vapor.

H261: In contact with water releases flammable gas.

H315: Causes skin irritation.

H319: Causes serious eye irritation. H335: May cause respiratory irritation.

Precautionary Statements

Prevention: P210: Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P223: Do not allow contact with water.

P231 + P232: Handle and store contents under inert gas. Protect

from moisture.

P233: Keep container tightly closed.

P240: Ground and bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting/handling

equipment.

P242: Use non-sparking tools.

P243: Take action to prevent static discharges.

P261: Avoid breathing sprays, mists, vapors or gases.

P264 + P265: Wash hands and exposed skin thoroughly after handling. Do not touch eyes.

P271: Use only outdoors or with adequate ventilation.

P280: Wear protective gloves/protective clothing/eye protection/

face protection/hearing protection.

Response: P302 + P335 + P334: IF ON SKIN: Brush off loose particles from skin and immerse in cool water.

P302 + P352: IF ON SKIN: Wash with plenty of water.

P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water.

P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P319: Get medical help if you feel unwell.

P332 + P317: If skin irritation occurs: Get medical help.

P337 + P317: If eye irritation persists: Get medical help.

P362 + P364: Take off contaminated clothing and wash it before reuse.

P370 + P378: In case of fire: Use dry chemical or carbon dioxide to extinguish. DO NOT USE FOAM OR WATER.

P402 + P404: Store in a dry place. Store in a closed container.

Storage:

Section 2. Hazards Identification

Storage (cont.): P403 + P233 + P235: Store in a well ventilated place. Keep

container tightly closed. Keep cool.

P405: Store locked up.

Disposal: P501: Dispose of contents/container in accordance with federal,

state and local regulations.

This material is considered hazardous by the OSHA Hazard **OSHA/HCS Status:**

Communication Standard (29 CFR 1910.1200).

Hazards Not Otherwise Classified (HNOC):

Reacts rapidly with water.

Section 3. Composition/Information on Ingredients

Substance Type: Mono-constituent.

Tetrakis(diethylamido)hafnium(IV); Hafnium Synonyms:

tetrakis(diethylazanide); Hafniumtetrakis(diethylazanid);

Diethyl[tris(diethylamino)hafnio]amine; TDEAH.

Formula: HfC₁₆H₄₀N₄ 626-554-9 EC-No.:

Component Name	%	CAS Number
Tetrakis(diethylamino)hafnium	≥ 99	19824-55-6

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First Aid Measures

Description of Necessary First Aid Measures

General Advice: Move out of dangerous area. If unconscious, place in recovery position and get

> medical help immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical help if symptoms develop or if you feel unwell. Show this safety data sheet to the doctor in attendance.

Immediately flush eyes with plenty of water, occasionally lifting the upper and **Eye Contact:**

lower eyelids. Check for and remove any contact lenses if easy to do. Continue

rinsing. Get medical help if eye irritation develops and persists.

Take off contaminated clothing and shoes immediately. Wash off contaminated **Skin Contact:**

skin with plenty of water. Get medical help if irritation develops and persists.

Rescuer should wear a mask or self-contained breathing apparatus if it is Inhalation:

suspected that fumes or gases are still present. Remove person to fresh air and

keep comfortable for breathing.

Section 4. First Aid Measures

Inhalation: If not breathing, if breathing is irregular or if respiratory arrest occurs, provide

> artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Do not use the mouth-to-mouth method of resuscitation if victim ingested or inhaled the product; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical devices. Get medical help

if symptoms develop or you feel unwell.

Ingestion: Do NOT induce vomiting. Remove dentures if any. If vomiting occurs, the

> head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If person is not breathing, if breathing is irregular or if respiratory arrest occurs, see the "Inhalation" first aid measures noted above. Get medical help if symptoms develop or you feel

unwell.

Most Important Symptoms/Effects, Acute and Delayed Potential Acute Health Effects

Symptoms may include stinging, tearing, redness, swelling and blurred vision. **Eye Contact: Skin Contact:** Symptoms may include an itching or burning sensation, reddening, swelling

and blistering with tissue necrosis.

Inhalation: Product may be irritating to respiratory system. Symptoms may include

coughing, sneezing with phlegm production, sore throat, nausea, headache,

vomiting.

Product may be expected to be irritating to mucous membranes. Symptoms Ingestion:

may include cramping, localized pain, headache, nausea and vomiting.

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary

Notes to Physician: Treat symptomatically.

No specific treatment. **Specific Treatments:**

Protection of First Responders: No action taken shall be taken involving any personal risk

without suitable training. It may be dangerous to the person

providing aid to give mouth-to-mouth resuscitation.

See Toxicological Information (Section 11)

Section 5. Fire Fighting Measures

General Hazards: Product reacts with water to release a highly flammable gas.

THE MOST EFFECTIVE FIRE EXTINGUISHING AGENT IS DRY **Suitable Extinguishing Media:**

CHEMICAL POWDER PRESSURIZED WITH NITROGEN.

Carbon dioxide (CO₂) may also be used.

DO NOT USE WATER OR FOAM. **Unsuitable Extinguishing Media:**

Ereztech HF4556 Page 4 of 16 Revision: 1.00

Section 5. Fire Fighting Measures

Unusual Fire and Explosion Hazards:

Product reacts with water and protic solvents to release a highly flammable gas which may form explosive mixtures with air at elevated temperatures. Product runoff to sewer may create a fire or explosion hazard. Gases released when product is exposed to moisture in air or water are heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to an ignition source and flashback.

Product of Combustion:

Carbon oxides (CO_X) , nitrogen oxides (NO_X) and hafnium oxides. Irritating fumes and organic acid vapors may be generated during exposure to elevated temperatures or open flame.

Protection of Firefighters:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Avoid contact with skin or eyes. Avoid the formation and inhalation of sprays, mists, vapors and gases.

Eliminate all local and distant ignition sources. Move containers from fire area if process can be accomplished without risk to firefighters. To reduce the possibility of explosion, use a water spray or fog to reduce direct vapors and to cool unopened containers. Do not apply water directly to product. Do not cut, grind, drill or weld on or near product containers (even empty) of this product because an explosion may result.

Fire-fighters should wear appropriate protection equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in a positive pressure mode.

Additional Information:

Prevent fire extinguishing water from contaminating surface waters or ground water systems.

Section 6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel:

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Eliminate all ignition sources (no smoking, flares, static discharge sources or flames in immediate area). Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid the formation and inhalation of sprays, mists, vapors and gases. Provide adequate ventilation. Wear respiratory protection. Put on appropriate personal protective equipment.

Section 6. Accidental Release Measures

For Emergency Responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For Non-Emergency Personnel".

Environmental Precautions:

Do not allow dispersal of spilled material and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for Containment General:

Spilled material will likely give off smoke and fumes. Eliminate all local and distant ignition sources. Move containers from spill area if safe to do so. Avoid the formation and inhalation of sprays, mists, vapors and gases. Avoid allowing the spilled material to get wet or using water to clean up spillages or residues. Use spark-proof tools and explosion-proof equipment. In the event of combustion: cover spillage with a dry, extinguishing material (e.g. dry sand, dry chemical, graphite powder) and allow time for decomposition or for fire to burn out (see Section 5 Firefighting Measures). Collect and place inert spillage in a dry, sealed container for disposal. Dispose of collected spillage in accordance with federal, state and local regulations. Contaminated absorbent material may pose the same hazard as the spilled product.

Small Spill:

Collect spillage with a dry, non-combustible, absorbent material (e.g. dry sand, vermiculite or diatomaceous earth) and place in dry, sealed container for disposal.

Large Spill:

Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with a dry, non-combustible, absorbent material (e.g. dry sand, vermiculite or diatomaceous earth) and place in dry, sealed container for disposal.

Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and Storage

Precautions:

Product reacts with water and moisture in the air to release a highly flammable gas; handle under a dry, inert gas. Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Keep away from all sources of ignition – NO SMOKING. Keep container tightly sealed.

Revision: 1.00 Ereztech HF4556 Page 6 of 16

Section 7. Handling and Storage

Precautions (cont.): Avoid contact with skin, eyes and clothing. Avoid the formation

> and inhalation of sprays, mists, vapors and gases. Do not ingest. Avoid prolonged exposure. Ensure adequate

ventilation.

Protect against electrostatic discharges. Use non-sparking tools **Protective Measures:**

> and explosion-proof electrical/ventilating/lighting/handling equipment. Put on appropriate personal protective equipment (see Section 8). Keep in the original container kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

General Occupational Hygiene: Eating, drinking and smoking should be prohibited in areas

> where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and

> smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for

additional information on hygiene measures.

Safe Storage Conditions: Product reacts with water and moisture in the air to release a

highly flammable gas; store under an inert gas. Nitrogen with less than 5 ppm each of moisture and oxygen and a

temperature range of 2 -8 °C is recommended. Keep away from all sources of ignition – NO SMOKING. Store in original container protected from direct sunlight in a dry and wellventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready

for use. Store locked up.

Section 8. Exposure Controls/Personal Protection

Introductory Remarks:

These recommendations provide general guidance for handling this product. Because work environments and material handling practices vary, safety procedures should be developed for each intended application. While developing safe handling procedures, do not overlook the need to clean equipment and conduct regular repairs. Waste from these procedures should be handled in accordance with Section 13.

Occupational Exposure Limits

Components	CAS-No.	List	Туре	Value
Tetrakis(diethylamino)hafnium	19824-55-6	ACGIH	TLV	0.5 mg/m ³ Hf TWA
		NIOSH	REL	0.5 mg/m ³ Hf TWA
				50 mg/m ³ Hf IDLH

Section 8. Exposure Controls/Personal Protection

Engineering Controls:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute. Provide an eyewash/shower station.

Environmental Exposure Controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Remove all soiled and contaminated clothing immediately. Avoid the formation and inhalation of sprays, mists, vapors and gases. Prevent contact with eyes and skin. Ensure that eyewash

Individual Protection Measures

Hygiene Measures:

stations and safety showers are close to the workstation location.

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, sprays or mists. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles, faceshield (8-inch minimum). Refer to 29 CFR 1910.133, ANSI Z87.1, or European Standard EN166.

Eye/Face Protection:

Skin Protection Hand Protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Chemical-resistant gloves.

Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product.

<u>Ereztech HF4556</u>

Page 8 of 16

Revision: 1.00

Date of Issue: 8/25/2025

Section 8. Exposure Controls/Personal Protection

Hand Protection (cont.): Dispose of contaminated gloves after use in accordance with

applicable laws and good laboratory practices. Wash and dry

hands. For full contact, use Neoprene or nitrile rubber.

Other Skin Protection: Appropriate footwear and any additional skin protection measures

> should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity discharges, wear anti-static, flame retardant protective clothing. For the greatest protection from static discharges, clothing should

include anti-static overalls, boots and gloves.

Where risk assessment shows air-purifying respirators are **Respiratory Protection:**

appropriate use a full-face respirator with multipurpose

combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate

government standards such as NIOSH (US) or CEN (EU).

Section 9. Physical and Chemical Properties

Physical State: Liquid.

Color: Light yellow.

No data available. Odor: **Odor Threshold:** No data available.

No data available. pH: -68 °C (-90.4 °F). **Melting Point:**

Boiling Point: 130 °C (266 °F) @ 0.01 hPa. **Flash Point:** 10 °C (50 °F) – closed cup.

Auto-ignition Temperature: No data available.

Specific Gravity: 1.249 g/ml @ 25 °C (lit).

No data available... **Vapor Pressure:** No data available. **Vapor Density:**

Water Solubility: Reacts to release highly flammable gases.

No data available. **Evaporation Rate:** No data available. **Viscosity:**

Section 10. Stability and Reactivity

This product reacts with water and protic solvents to Reactivity:

release a highly flammable gas.

This product is stable when stored under a dry, inert **Chemical Stability:**

> atmosphere and away from heat. Nitrogen containing less than 5 ppm each moisture and air and a temperature

range of 2 – 8 °C is recommended.

Conditions to Avoid: Exposure to water/moisture, sources of ignition (heat,

flames, sparks, electrostatic discharges), extremes of

temperature and direct sunlight.

Strong oxidizing agents. **Incompatible Materials:**

Hazardous Decomposition Products: Hazardous decomposition products formed under fire

> conditions: diethylamine, carbon oxides (CO_X), nitrogen oxides (NO_x), and hafnium oxide fumes. Irritating fumes

and organic acid vapors may be generated during

exposure to elevated temperatures or open flame. In the

event of a fire: see Section 5.

Possibility of Hazardous Reactions: Under normal conditions of storage and use noted above,

hazardous reactions will not occur. Hazardous reactions or instability may occur under certain conditions of storage or use. In contact with water, product releases highly

flammable gases.

Section 11. **Toxicological Information**

Information on Toxicological Effects

No specific data available. Product may be harmful if **Acute Toxicity:**

ingested or inhaled.

Irritation/Corrosion: No specific data available. Product causes skin irritation

and serious eye irritation.

Sensitization: No specific data available. **Germ Cell Mutagenicity:** No specific data available.

Carcinogenicity

Component	CAS No	ACGIH	IARC	NTP	OSHA
Tetrakis(diethylamino)hafnium	19824-55-6	Not listed	Not listed	Not listed	Not listed

Reproductive Toxicity: No specific data available. Teratogenicity: No specific data available.

Specific Target Organ Toxicity:

(Single Exposure)

Product may cause respiratory tract irritation.

Section 11. Toxicological Information

Specific Target Organ Toxicity:

(Repeated Exposure)

Routes of Exposure:

No specific data available.

Aspiration Hazard:

No specific data available.

Information on the Likely

Common routes of exposure: inhalation, dermal (failure to use skin protection), eye (failure to use safety

eyewear). Less common: ingestion (failure to employ

recommended hygiene measures (e.g. smoking or eating after handling product without washing hands or using

hand protection).

To the best of our knowledge, the chemical, physical and **Additional Information:**

toxicological properties of this product have not been

thoroughly investigated.

Section 12. Ecological Information

Ecotoxicity:

When exposed to water, product releases a substance which is harmful aquatic organisms and may cause longterm adverse effects in the aquatic environment.

Aquatic Toxicity (Acute)

Component	CAS No	Test	Species	Dose	Exposure
Diethylamine	109-89-7	LC50	Fish (Rainbow trout)	25 mg/l	96 h
BRIDG		EC50	Water flea	100 mg/l	48 h
5 71 1 5 6.		EC50	Algae	20 mg/l	96 h

Persistence and Degradability

Biodegradability: No specific data available. **Bioaccumulative Potential:** No specific data available. **Mobility in Soil:** No specific data available.

Results of PBT and vPvB Assessment: PBT/vPvB assessment not available as chemical safety

assessment not required/not conducted.

No specific data available. **Endocrine Disrupting Properties:**

Other Adverse Effects: An environmental hazard cannot be excluded in the event

of unprofessional handling or disposal.

Section 13. Disposal Considerations

Waste Treatment Methods

Product: Dispose of in accordance with local, state, and federal

regulations. Refer to 40 CFR 260-299 for complete waste disposal regulations. Consult your local, state, or federal

agency before disposing of any chemicals.

Contaminated Packaging: Empty containers retain product residue (liquids, vapors,

gases) and can be dangerous. Dispose of as unused containers. DO NOT EXPOSE SUCH CONTAINERS TO

AIR, MOISTURE, HEAT, FLAME, SPARKS, STATIC

ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY

MAY EXPLODE AND CAUSE INJURY OR DEATH.

Section 14. Transport Information

	DOT	IMDG	IATA
UN Number	UN3399	UN3399	UN3399
UN Proper Shipping Name	Organometallic substance, liquid, water- reactive, flammable (Tetrakis(diethylamino) hafnium)	ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE (Tetrakis(diethylamino) hafnium)	Organometallic substance, liquid, water- reactive, flammable (Tetrakis(diethylamino) hafnium)
Transport	4.3 (3)	4.3 (3)	4.3 (3)
Hazard Classes	IDGING C	HEMICAL	GAPS -
Packing Group	II	H	II
Environmenta I Hazards	-	-	-
Additional Information	-	EMS-No: F-G, S-N	-

Special Precautions for User:

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory Information

Toxic Substance Control Act (TSCA)

This product is not listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory). Use of this product is restricted to research and development only. This product must be used under the supervision of a technically qualified individual as defined by the TSCA. This product must not be used for commercial purposes or in formulations for commercial purposes.

This product as supplied is not subject to the TSCA Significant New Use Rule.

This product as supplied is not subject to TSCA 12(b) export notification requirements.

SARA 302 Components

This product does not contain any components which are subject to the reporting requirements of SARA Title III, Section 302 EHS TPQ.

SARA 304 Components

This product does not contain any components which are subject to the reporting requirements of SARA Title III, Section 304 RQ.

SARA 311/312 Hazards

Fire Hazard (Flammable liquid), Reactivity Hazard (In contact with water emits flammable gas), Acute Health Hazard (Acute toxicity – ingestion; Skin corrosion or irritation; Serious eye damage or eye irritation; Specific Target Organ Toxicity (STOT), single exposure: respiratory irritation).

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

Not applicable.

Clean Air Act

Not applicable.

CERCLA Reportable Quantity

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US Department of Homeland Security (DHS)

This product does not contain any DHS chemicals.

US Department of Transportation (DOT)

Component	Reportable Quantity	DOT Marine Pollutant	DOT Severe Marine Pollutant
Tetrakis(diethylamino)hafnium	No	No	No

Section 15. Regulatory Information

US State Right-to-Know Listings

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Tetrakis(diethylamino)hafnium	-	-	-	-	-

[&]quot;X" - Listed.

US State Chemicals of High Concern Listings

Component	Maine	Vermont	Washington
Tetrakis(diethylamino)hafnium	-	-	-

[&]quot;X" - Listed.

California Proposition 65 Components

This product does not contain any Proposition 65 chemicals.

Section 16. Other Information



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright © 2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

HMIS Rating

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	2

Section 16. Other Information

History

Date of Issue/Date of Revision: 8/25/2025.

Date of Previous Issue: None.

None available References:

Abbreviations and Acronyms

ACGIH : American Conference of Governmental Industrial Hygienists.

AIHA American Industrial Hygiene Association.

ATE Acute Toxicity Estimate (per Chapter 3.1 of GHS 10 standard).

BEI Biological Exposure Indices (ACGIH).

CAS : Chemical Abstracts Service (division of the American Chemical Society).

CHRIS : Chemical Hazards Response Information System (US DOT). CLP : Classification, Labeling and Packaging (European Union (EU)).

DOT : US Department of Transportation.

EC-No. : The EC Inventory (EINECS, ELINCS and the NLP-list is the source of the seven digit

EC number, an identifier of substances commercially available with the EU (European

Union).

EINECS : European Inventory of Existing Commercial Chemical Substances.

: Extremely Hazardous Substance. EHS

: European List of Notified Chemical Substances. **ELINCS**

: Globally Harmonized System of Classification and Labeling of Chemicals. GHS

Hazardous Air Pollutants (Clean Air Act). HAP : Hazardous Materials Identification System. **HMIS**

: Hazards Not Otherwise Classified. **HNOC**

IARC International Agency for Research on Cancer.

IATA International Air Transport Association.

Dangerous Goods Regulations by the "International Air Transport Association" IATA-DGR

(IATA).

IDLH : Immediately Dangerous to Life or Health (US National Institute for Occupation Health

and Safety (NIOSH)).

: International Maritime Code for Dangerous Goods. **IMDG**

IΡ Intraperitoneal. IV Intravenous.

NFPA National Fire Protection Association.

NIOSH National Institute of Occupational Safety and Health.

NSRL No Significant Risk Levels. NTP National Toxicology Program.

Ozone Depleting Substances (US Clean Air Act). ODS

OECD Organization for Economic Co-Operation and Development.

OFL Occupational Exposure Limit.

Occupational Safety and Health Administration. OSHA

Persistent Bioaccumulative and Toxic. **PBT**

PEL Permissible Exposure Limits.

Section 16. Other Information

Abbreviations and Acronyms (cont.)

REL : Recommended Exposure Limits.

RQ : Reportable Quantity.

SARA : Superfund Amendments and Reauthorization Act.

STEL (ST) : Short Term Exposure Limit (ACGIH/NIOSH)

STOT : Specific Target Organ Toxicity.
 TLV : Threshold Limit Values (ACGIH).
 TPQ : Threshold Planning Quantity.
 TWA : Time Weighted Average.
 VOC : Volatile Organic Compound.

vPvB : Very Persistent and Very Bioaccumulative.

WEEL : Workplace Environmental Exposure Level (AIHA).

Disclaimer

The information herein is believed to be accurate and is presented in good faith; however, no warranties or representations are made by Ereztech LLC regarding the accuracy or completeness of the information. Ereztech LLC shall not be liable for any damages resulting from the handling, or from the contact with the above product.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Ereztech HF4556 Page 16 of 16 Revision: 1.00