



SAFETY DATA SHEET

Section 1. Identification

Product Name:	Nickel(II) 1-dimethylamino-2-methyl-2-butoxide
Product Type:	Liquid
CAS Number:	942311-35-5
Product Number:	NI1355
Product Manufacturer:	Ereztech LLC 11555 Medlock Bridge Road, Suite 100 Johns Creek, GA 30097
Product Information:	(888) 658-1221
<u>In Case of an Emergency:</u>	CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International); CCN836180 *** Contact manufacturer for all non-emergency calls.

Section 2. Hazards Identification

Appearance/Odor:	Dark green liquid, odor not determined.
Classification:	SKIN CORROSION/IRRITATION - Category 2, H315 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A, H319 SENSITIZATION, RESPIRATORY - Category 1, H334 SPECIFIC ORGAN TOXICITY, SINGLE EXPOSURE; RESPIRATORY TRACT IRRITATION - Category 3, H335 SPECIFIC ORGAN TOXICITY, REPEATED EXPOSURE - Category 1, H372

GHS Label Elements

Hazard Pictograms:



Signal Word:	DANGER.
Hazard Statements:	H315: Causes skin irritation. H319: Causes serious eye irritation. H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Nickel(II) 1-dimethylamino-2-methyl-2-butoxide

Safety Data Sheet

Section 2. Hazards Identification

Hazard Statements (cont.):	H335: May cause respiratory irritation. H372: Causes damage to organs (lungs, liver, kidneys, respiratory system) through prolonged or repeated exposure.
<u>Precautionary statements</u>	
Prevention:	P260: Do not breathe fumes/mists/vapors/sprays. P264: Wash skin thoroughly after handling. P270: Do not eat, drink or smoke when using this product. P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves/ protective clothing/ eye protection/ face protection. P285: In case of inadequate ventilation, wear respiratory protection.
Response:	P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present. Continue rinsing. P311 + P342: If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. P312: Call a POISON CENTER or doctor/physician if you feel unwell. P314: Get medical advice/attention if you feel unwell. P332 + P313: If skin irritation occurs: Get medical advice/attention. P337 + P313: If eye irritation persists: Get medical advice/attention. P362: Take off contaminated clothing and wash before reuse.
Storage:	P403 + P233: Store in a well ventilated place. Keep container tightly closed. P405: Store locked up.
Disposal:	P501: Dispose of contents/ container to an approved waste disposal plant.
OSHA/HCS Status:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Hazards Not Otherwise Classified (HNOC):	Reacts with water to release flammable gases.

Section 3. Composition/Information on Ingredients

Substances

Synonyms : Bis(1-dimethylamino-2-methyl-2-butoxy)nickel(II); bis(1-dimethylamino-2-methyl-2-butoxide)nickel(II).

Nickel(II) 1-dimethylamino-2-methyl-2-butoxide

Safety Data Sheet

Section 3. Composition/Information on Ingredients

Formula : C₁₄H₃₂N₂O₂Ni
Molecular Weight : 319.13 g/mol.
CAS-No. : 942311-35-5

Ingredient Name	%	CAS Number
Nickel(II) 1-dimethylamino-2-methyl-2-butoxide	>98	942311-35-5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First Aid Measures

Description of Necessary First Aid Measures

General Advice: Move out of dangerous area. Call a physician or POISON CONTROL CENTER immediately if inhaled or ingested. Show this safety data sheet to the doctor in attendance.

Eye Contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue rinsing. Seek medical attention if eye irritation develops and persists.

Skin Contact: Wash off contaminated skin with soap and plenty of water. Seek medical attention if irritation develops and persists or if burns occur.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Call a POISON CENTER or doctor/physician immediately.

Ingestion: Rinse mouth. Do NOT induce vomiting. Remove dentures if any. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Call a physician or POISON CONTROL CENTER immediately.

Most Important Symptoms/Effects, Acute And Delayed Potential Acute Health Effects

Eye Contact: Symptoms may include stinging, tearing, redness, swelling and blurred vision.

Inhalation: Product may be irritating to respiratory system and may cause allergy-like or asthma-like symptoms. Symptoms may include coughing, sore throat, difficulty breathing, tightness in chest, nausea, headache, vomiting.

Skin Contact: Symptoms may include an itching or burning sensation, reddening, swelling and blistering with tissue necrosis.

Nickel(II) 1-dimethylamino-2-methyl-2-butoxide

Safety Data Sheet

Section 4. First Aid Measures

Ingestion: Symptoms may include abdominal pain, diarrhea, headaches, shortness of breath, nausea and vomiting.

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary

Notes to Physician: Treat symptomatically.

Specific Treatments: No specific treatment.

Protection of First Responders: No action taken shall be taken involving any personal risk without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire Fighting Measures

General Hazards: Product reacts with water to produce a flammable liquid and vapors.

Suitable Extinguishing Media: THE MOST EFFECTIVE FIRE EXTINGUISHING AGENT IS DRY CHEMICAL POWDER PRESSURIZED WITH NITROGEN. For small fires, vermiculite, sand, dry chemical or carbon dioxide (CO₂) may also be used.

Unsuitable Extinguishing Media: DO NOT USE WATER OR FOAM as product reacts to produce flammable vapors upon contact with water.

Unusual Fire and Explosion Hazards: This material reacts with water and compounds containing active hydrogen such as alcohols and acids to produce flammable gases. Product runoff to sewer may create a fire or explosion hazard. Vapor/gases are heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to an ignition source and flashback.

Product of Combustion: Decomposition products include carbon oxides (CO_x), nitrogen oxides (NO_x) and nickel oxides.

Protection of Firefighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Avoid contact with skin or eyes. Avoid breathing dusts, aerosols, vapors and gases.
Eliminate all local and distant ignition sources. Move containers from fire area if process can be accomplished without risk to firefighters. Do not cut, grind, drill or weld on or near product containers (even empty) of this product because an explosion may result.

Nickel(II) 1-dimethylamino-2-methyl-2-butoxide

Safety Data Sheet

Section 5. Fire Fighting Measures

Protection of Firefighters (cont.): Fire-fighters should wear appropriate protection equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

Section 6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid the formation and inhalation of sprays, mists, vapors and gases. Provide adequate ventilation. Wear respiratory protection. Put on appropriate personal protective equipment.

For Emergency Responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental Precautions: Do not allow dispersal of spilled material and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for Containment

General: Eliminate all local and distant ignition sources. Move containers from spill area if safe to do so. Avoid allowing the spilled material to get wet or using water to clean up spillages or residues. Use spark-proof tools and explosion-proof equipment.

Small Spill: Contain and collect spillage with non-combustible, dry absorbent material (e.g. sand, earth, vermiculite or diatomaceous earth) and place in dry, sealed container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor.

Large Spill: Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, dry absorbent material (e.g. sand, earth, vermiculite or diatomaceous earth) and place in dry, sealed container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

Nickel(II) 1-dimethylamino-2-methyl-2-butoxide

Safety Data Sheet

Section 6. Accidental Release Measures

Large Spill (cont.):

Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and Storage

Precautions:

Product is moisture sensitive; handle under a dry, inert gas. Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Keep away from all sources of ignition – NO SMOKING. Keep container tightly sealed. Avoid contact with skin, eyes and clothing. Avoid the formation and inhalation of sprays, mists, vapors and gases. Do not ingest. Avoid prolonged exposure. Ensure adequate ventilation.

Protective Measures:

Put on appropriate personal protective equipment (see Section 8). Keep in the original container kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

General Occupational Hygiene:

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Safe Storage Conditions:

Product is moisture sensitive; store under an inert gas. Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Store refrigerated at 2 – 8 °C. Keep away from all sources of ignition – NO SMOKING. Store in original container protected from direct sunlight in a dry and well-ventilated area, away from incompatible materials noted above and food and drink. Keep container tightly closed and sealed until ready for use. Store locked up.

Section 8. Exposure Controls/Personal Protection

Introductory Remarks:

These recommendations provide general guidance for handling this product. Because work environments and material handling practices vary, safety procedures should be developed for each intended application. While developing safe handling procedures, do not overlook the need to clean equipment and conduct regular repairs. Waste from these procedures should be handled in accordance with Section 13.

Nickel(II) 1-dimethylamino-2-methyl-2-butoxide

Safety Data Sheet

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits:

List	Components	CAS-No.	Type	Value
ACGIH	Nickel, soluble compounds as Ni	7440-02-0	TLV	0.1 mg/m ³ TWA (Inhalation)
NIOSH	Nickel, soluble compounds as Ni	7440-02-0	REL	0.015 mg/m ³ TWA – 10 hrs.
OSHA	Nickel, soluble compounds as Ni	7440-02-0	OEL (Z1)	0.1 mg/m ³ TWA

Engineering Controls:

Properly operating explosion-proof, chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute. Provide an eyewash/shower station.

Environmental Exposure Controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual Protection Measures

Hygiene Measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Remove all soiled and contaminated clothing immediately. Avoid the formation and inhalation of sprays, mists, aerosols, vapors and gases. Avoid contact with eyes and skin. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/Face Protection:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to aerosols, vapors or sprays. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles, faceshield (8-inch minimum). Refer to 29 CFR 1910.133, ANSI Z87.1, or European Standard EN166.

Skin Protection

Hand Protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties.

Nickel(II) 1-dimethylamino-2-methyl-2-butoxide

Safety Data Sheet

Section 8. Exposure Controls/Personal Protection

Hand Protection (cont.):

It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Chemical-resistant gloves. For full contact, wear Neoprene or nitrile rubber gloves.

Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Other Skin Protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory Protection:

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Section 9. Physical and Chemical Properties

Physical State:	Liquid.
Color:	Dark green.
Odor:	No data available.
Odor Threshold:	No data available.
pH:	No data available.
Melting Point:	<10 °C (<50 °F).
Boiling Point:	148 °C (298.4 °F) at 3.32 Torr.
Flash Point:	140 °C (284 °F) – Cleveland open cup.
Specific Gravity:	No data available.
Vapor Pressure:	0.1 Torr at 80 °C.
Vapor Density:	No data available.

Nickel(II) 1-dimethylamino-2-methyl-2-butoxide

Safety Data Sheet

Section 9. Physical and Chemical Properties

Water Solubility: Reacts with water to produce flammable liquid and vapors.

Section 10. Stability and Reactivity

Reactivity: This product reacts with water and compounds containing active hydrogen such as alcohols and acids to release highly flammable gases.

Chemical Stability: This product is stable when stored under a dry, inert atmosphere and away from heat. Nitrogen containing less than 5 ppm each moisture and air and a temperature range of 2 – 8 °C is recommended. This product is not sensitive to impact.

Conditions to Avoid: Exposure to water/moisture, sources of ignition (heat, flames, sparks, electrostatic discharge), extremes of temperature and direct sunlight.

Incompatible Materials: Water, compounds containing active hydrogen (alcohols, acids) and strong oxidizing agents.

Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products formed under fire conditions: carbon oxides, nitrogen oxides and nickel oxide fumes. Irritating fumes and organic acid vapors may be generated during exposure to elevated temperatures or open flame. In the event of a fire: see section 5.

Possibility of Hazardous Reactions: Under normal conditions of storage and use noted above, hazardous reactions will not occur. Hazardous reactions or instability may occur under certain conditions of storage or use. Product reacts with water to produce a flammable liquid and vapors.

Section 11. Toxicological Information

Information on Toxicological Effects

- | | |
|-------------------------------|--|
| Acute Toxicity | : No specific data available. Product may be harmful if inhaled or ingested. |
| Irritation/Corrosion | : Product causes skin irritation and serious eye irritation. |
| Sensitization | : Product may cause allergy or asthma symptoms if inhaled. |
| Germ Cell Mutagenicity | : No effects known. |

Nickel(II) 1-dimethylamino-2-methyl-2-butoxide

Safety Data Sheet

Section 11. Toxicological Information

Carcinogenicity

- IARC** : No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- ACGIH** : No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by ACGIH.
- NTP** : No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by NTP.
- OSHA** : No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by OSHA.

Reproductive Toxicity

- : This product is not expected to cause reproductive or developmental effects.

Teratogenicity

- : No specific data available.

Specific Target Organ Toxicity (Single Exposure)

- : No specific data available.

Specific Target Organ Toxicity (Repeated Exposure)

- : May cause damage to lungs, kidneys, liver and respiratory system with repeated exposure.

Aspiration Hazard

- : No specific data available.

Information on the Likely Routes of Exposure

- : Common routes of exposure: inhalation, dermal (failure to use skin protection), eye (failure to use safety eyewear). Less common: ingestion (failure to employ recommended hygiene measures (e.g. smoking or eating after handling product without washing hands or using hand protection)).

Additional Information

- : May be harmful if inhaled or ingested. Material is destructive to the tissue of the mucous membranes and upper respiratory tract.

To the best of our knowledge, the chemical, physical and toxicological properties of this product have not been thoroughly investigated.

Section 12. Ecological Information

Numerical Measures of Toxicity

Toxicity to Fish

- : No specific data available.

Toxicity to Daphnia and Other

- : No specific data available.

Nickel(II) 1-dimethylamino-2-methyl-2-butoxide

Safety Data Sheet

Section 12. Ecological Information

Aquatic Invertebrates

Toxicity to Algae : No specific data available.

Persistence and Degradability

Biodegradability : No specific data available.

Bioaccumulative Potential : No specific data available.

Mobility in Soil : No specific data available.

Other Adverse Effects : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13. Disposal Considerations

Waste Treatment Methods

Product Dispose of in accordance with local, state, and federal regulations. Refer to 40 CFR 260-299 for complete waste disposal regulations. Consult your local, state, or federal agency before disposing of any chemicals.

Contaminated Packaging Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Dispose of as unused product.

Section 14. Transport Information

	DOT	IMDG	IATA
UN Number	UN 3398	UN 3398	UN 3398
UN Proper Shipping Name	Organometallic substance, liquid, water-reactive, (Nickel(II) 1-dimethylamino-2-methyl-2-butoxide)	ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, (Nickel(II) 1-dimethylamino-2-methyl-2-butoxide)	Organometallic substance, liquid, water-reactive, (Nickel(II) 1-dimethylamino-2-methyl-2-butoxide)
Transport Hazard Classes	4.3	4.3	4.3
Packing Group	II	II	II
Environmental Hazards	No	No	No
Additional Information	-	EMS-No: F-G, S-N	-

Special Precautions for User : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Nickel(II) 1-dimethylamino-2-methyl-2-butoxide

Safety Data Sheet

Section 14. Transport Information

Transporting in Bulk According to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

Section 15. Regulatory Information

TSCA (Toxic Substance Control Act):

This product is not listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory). Use of this product is restricted to research and development only. This product must be used under the supervision of a technically qualified individual as defined by the TSCA. This product must not be used for commercial purposes or in formulations for commercial purposes.

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Acute Health Hazard (Skin corrosion or irritation; Serious eye damage or eye irritation; Respiratory sensitization; Specific target organ toxicity (STOT), single exposure: respiratory irritation); Chronic Health Hazard (Specific target organ toxicity (STOT), repeated exposure: organ damage).

Massachusetts Right to Know Components

No components are subject to Massachusetts Right to Know Act.

Pennsylvania Right to Know Components

No components are subject to Pennsylvania Right to Know Act.

New Jersey Right to Know Components

No components are subject to New Jersey Right to Know Act.

California Proposition 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Nickel(II) 1-dimethylamino-2-methyl-2-butoxide

Safety Data Sheet

Section 16. Other Information

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

HMIS Rating

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	2

History

Date of Printing	: 3/27/2020
Date of Issue/Date of Revision	: 3/27/2020
Date of Previous Issue	: 1/25/2020
References	: None available.

Abbreviations and Acronyms

- ACGIH: American Conference of Governmental Industrial Hygienists.
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstracts Service (division of the American Chemical Society).
- DOT: US Department of Transportation.
- GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
- HMIS: Hazardous Materials Identification System.
- IARC: International Agency for Research on Cancer.
- IATA: International Air Transport Association.
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA).

Nickel(II) 1-dimethylamino-2-methyl-2-butoxide

Safety Data Sheet

Section 16. Other Information

Abbreviations and Acronyms (cont.)

IDLH: Immediately Dangerous to Life or Health (US National Institute for Occupation Health and Safety (NIOSH)).

IMDG: International Maritime Code for Dangerous Goods.

NFPA: National Fire Protection Association.

NIOSH: National Institute of Occupational Safety and Health.

NTP: National Toxicology Program.

OSHA: Occupational Safety and Health Administration.

PEL: Permissible Exposure Limits.

REL: Recommended Exposure Limits.

SARA: Superfund Amendments and Reauthorization Act.

STOT: Specific Target Organ Toxicity.

TLV: Threshold Limit Values (ACGIH).

TWA: Time Weighted Average.

VOC: Volatile Organic Compound.

Disclaimer

The information herein is believed to be accurate and is presented in good faith; however, no warranties or representations are made by Ereztech LLC regarding the accuracy or completeness of the information. Ereztech LLC shall not be liable for any damages resulting from the handling, or from the contact with the above product.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

BRIDGING CHEMICAL GAPS