



SAFETY DATA SHEET

Section 1. Identification

Product Name:	Tantalum, tetraethoxy(hydrogen acetoacetato)-, ester
Product Type:	Solid
CAS Number:	17348-27-5
Product Number:	TA8275
Product Manufacturer:	Ereztech LLC 11555 Medlock Bridge Road, Suite 100 Johns Creek, GA 30097
Product Information:	(888) 658-1221
<u>In Case of an Emergency:</u>	CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International); CCN836180 *** Contact manufacturer for all non-emergency calls.

Section 2. Hazards Identification

Appearance/Odor:	Solid, odor not determined.
Classification:	FLAMMABLE SOLIDS - Category 2, H228 SKIN CORROSION/IRRITATION - Category 2, H315 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A, H319 SPECIFIC ORGAN TOXICITY, SINGLE EXPOSURE; RESPIRATORY TRACT IRRITATION - Category 3, H335

GHS Label Elements

Hazard Pictograms:



Signal Word:	WARNING
Hazard Statements:	H228: Flammable solid. H315: Causes skin irritation. H319: Causes serious eye irritation. H335: May cause respiratory irritation.

Tantalum, tetraethoxy(hydrogen acetoacetato)-, ester

Safety Data Sheet

Section 2. Hazards Identification

Precautionary Statements

Prevention:

P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P240: Ground/bond container and receiving equipment.
P241: Use explosion proof electrical/ventilating/lighting/equipment.
P261: Avoid breathing fumes/gas/mist/vapor/spray.
P264: Wash skin thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352: IF ON SKIN: Wash with plenty of soap and water.
P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present. Continue rinsing.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P332 + P313: If skin irritation occurs: Get medical advice/attention.
P337 + P313: If eye irritation persists: Get medical advice/attention.
P362: Take off contaminated clothing and wash before reuse.
P370 + P378: In case of fire: Use alcohol-resistant foam, dry chemical or carbon dioxide for extinction.

Storage:

P403 + P233: Store in a well ventilated place. Keep container tightly closed.

Disposal:

P405: Store locked up.

P501: Dispose of contents/ container to an approved wasted disposal plant.

General:

None.

OSHA/HCS Status:

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Hazards Not Otherwise Classified (HNOC):

Reacts with water and moist air to release ethanol.

Section 3. Composition/Information on Ingredients

Substances

Molecular Formula : C₁₄H₂₉O₂Ta
Molecular Weight : 410.31 g/mol
CAS-No. : 17348-27-5

Tantalum, tetraethoxy(hydrogen acetoacetato)-, ester

Safety Data Sheet

Section 3. Composition/Information on Ingredients

Ingredient Name	%	CAS Number
Tantalum, tetraethoxy(hydrogen acetoacetato)-, ester	≥ 98	17348-27-5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First Aid Measures

Description of Necessary First Aid Measures

- General Advice:** Move out of dangerous area. Call a POISON CENTER or doctor/physician immediately if symptoms develop or if you feel unwell. Show this safety data sheet to the doctor in attendance.
- Eye Contact:** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue rinsing. Seek medical attention if eye irritation develops and persists.
- Skin Contact:** Take off contaminated clothing and shoes immediately. Wash off contaminated skin with soap and plenty of water. Seek medical attention if irritation develops and persists or if burns occur.
- Inhalation:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Call a physician or POISON CONTROL CENTER if symptoms develop or if you feel unwell.
- Ingestion:** Rinse mouth. Do NOT induce vomiting. Remove dentures if any. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Call a physician or POISON CONTROL CENTER if symptoms develop or if you feel unwell.

Most Important Symptoms/Effects, Acute and Delayed Potential Acute Health Effects

- Eye Contact:** Symptoms may include stinging, tearing, redness, swelling and blurred vision.
- Inhalation:** Product may be irritating to respiratory system. Symptoms may include coughing, sneezing with phlegm production, sore throat, nausea, headache, vomiting.
- Skin Contact:** Symptoms may include an itching or burning sensation, reddening, swelling and blistering with tissue necrosis.

Tantalum, tetraethoxy(hydrogen acetoacetato)-,ester

Safety Data Sheet

Section 4. First Aid Measures

Ingestion: Product may be expected to be irritating to mucous membranes. Symptoms may include cramping, localized pain, headache, nausea and vomiting.

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary

Notes to Physician: Treat symptomatically.

Specific Treatments: No specific treatment.

Protection of First Responders: No action taken shall be taken involving any personal risk without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See Toxicological Information (Section 11)

Section 5. Fire Fighting Measures

General Hazards: Flammable solid. Fire may produce irritating fumes and organic acid vapors.

Suitable Extinguishing Media: THE MOST EFFECTIVE FIRE EXTINGUISHING AGENT IS DRY CHEMICAL POWDER PRESSURIZED WITH NITROGEN. For small fires, vermiculite, sand, dry chemical or carbon dioxide (CO₂) may also be used. For large fires, large quantities of water (flooding) may be applied as a spray or a mist to control the fire and cool affected containers.

Unsuitable Extinguishing Media: Do not use water jet as an extinguisher as it may scatter and spread the fire.

Unusual Fire and Explosion Hazards: Vapor/air mixtures are explosive above flash point. Product runoff to sewer may create a fire or explosion hazard. Vapors/gases released under fire conditions are heavier than air and may spread long distances along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to an ignition source and flashback. Containers may explode when heated.

Product of Combustion: Carbon oxides (CO_x) and tantalum oxides. Irritating fumes and organic acid vapors may be generated during exposure to elevated temperatures or open flame.

Protection of Firefighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Avoid contact with skin or eyes. Avoid breathing dusts, aerosols, vapors and gases.

Eliminate all local and distant ignition sources. Move containers from fire area if process can be accomplished without risk to firefighters.

Tantalum, tetraethoxy(hydrogen acetoacetato)-, ester

Safety Data Sheet

Section 5. Fire Fighting Measures

Protection of Firefighters (cont.): To reduce the possibility of explosion, use a water spray or fog to reduce direct vapors and to cool unopened containers. Do not cut, grind, drill or weld on or near product containers (even empty) of this product because an explosion may result.

Fire-fighters should wear appropriate protection equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

Section 6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid the formation and inhalation of dusts and aerosols. Provide adequate ventilation. Wear respiratory protection. Put on appropriate personal protective equipment.

For Emergency Responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For Non-Emergency Personnel".

Environmental Precautions: Do not allow dispersal of spilled material and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for Containment

General: Eliminate all local and distant ignition sources. Move containers from spill area if safe to do so. Use spark-proof tools and explosion-proof equipment.

Small Spill: Contain and collect spillage with a dry, non-combustible binding material (e.g. sand, earth, vermiculite or diatomaceous earth) and place in dry, sealed container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor.

Tantalum, tetraethoxy(hydrogen acetoacetato)-, ester

Safety Data Sheet

Section 6. Accidental Release Measures

Large Spill:

Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with a dry, non-combustible binding material (e.g. sand, earth, vermiculite or diatomaceous earth) and place in dry, sealed container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and Storage

Precautions:

Product is moisture sensitive; handle under a dry, inert gas. Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Keep away from all sources of ignition – NO SMOKING. Keep container tightly sealed. Avoid contact with skin, eyes and clothing. Avoid the formation and inhalation of dusts, aerosols, vapors and gases. Do not ingest. Avoid prolonged exposure. Ensure adequate ventilation.

Protective Measures:

Protect against electrostatic charges. Use explosion-proof electrical/ventilating/lighting/handling equipment. Use only non-sparking tools and equipment. Put on appropriate personal protective equipment (see Section 8). Keep in the original container kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

General Occupational Hygiene:

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Safe Storage Conditions:

Product is moisture sensitive; store under an inert gas. Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Keep away from all sources of ignition – NO SMOKING. Store in original container protected from direct sunlight in a dry and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Store locked up.

Tantalum, tetraethoxy(hydrogen acetoacetato)-, ester

Safety Data Sheet

Section 8. Exposure Controls/Personal Protection

Introductory Remarks:

These recommendations provide general guidance for handling this product. Because work environments and material handling practices vary, safety procedures should be developed for each intended application. While developing safe handling procedures, do not overlook the need to clean equipment and conduct regular repairs. Waste from these procedures should be handled in accordance with Section 13.

Occupational Exposure Limits

List	Components	CAS-No.	Type	Value
OSHA	Penta-sec-butoxy tantalum	6382-80-5	PEL	5 mg/m ³ (Ta metal) - TWA
ACGIH	Ethanol	64-17-5	STEL	100 ppm (TLV)
NIOSH			REL	1,900 mg/m ³ 1000 ppm (TWA)
OSHA			PEL	1,900 mg/m ³ 1000 ppm (TWA)

Engineering Controls:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute. Provide an eyewash/shower station.

Environmental Exposure Controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual Protection Measures

Hygiene Measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Remove all soiled and contaminated clothing immediately. Do not inhale dusts/aerosols/vapors/gases. Avoid contact with eyes and skin. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/Face Protection:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles, faceshield (8-inch minimum). Refer to 29 CFR 1910.133, ANSI Z87.1, or European Standard EN166.

Tantalum, tetraethoxy(hydrogen acetoacetato)-, ester

Safety Data Sheet

Section 8. Exposure Controls/Personal Protection

Skin Protection

Hand Protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Chemical-resistant gloves.

Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. For full contact, wear Neoprene or nitrile rubber gloves.

Other Skin Protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory Protection:

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Section 9. Physical and Chemical Properties

Physical State:

Solid.

Color:

No data available.

Odor:

No data available.

Odor Threshold:

No data available.

pH:

No data available.

Melting Point:

No data available.

Tantalum, tetraethoxy(hydrogen acetoacetato)-, ester

Safety Data Sheet

Section 9. Physical and Chemical Properties

Boiling Point:	No data available.
Flash Point:	No data available.
Auto-ignition temperature:	No data available.
Density:	No data available.
Vapor Pressure:	No data available.
Vapor Density:	No data available.
Water Solubility:	No data available.
Evaporation Rate:	No data available.
Viscosity:	No data available.

Section 10. Stability and Reactivity

Reactivity:	No data available.
Chemical Stability:	This product is stable when stored under a dry, inert atmosphere and away from heat. Nitrogen containing less than 5 ppm each moisture and air and a temperature range of 2 – 8 °C is recommended. This product is not sensitive to impact.
Conditions to Avoid:	Exposure to water/moisture, sources of ignition (heat, flames, sparks, electrostatic discharge), extremes of temperature and direct sunlight.
Incompatible Materials:	Strong oxidizing agents.
Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products formed under fire conditions: carbon oxides (CO _x) and tantalum oxide fumes. Irritating fumes and organic acid vapors may be generated during exposure to elevated temperatures or open flame. In the event of a fire: see section 5.
Possibility of Hazardous Reactions:	Under normal conditions of storage and use noted above, hazardous reactions will not occur. Hazardous reactions or instability may occur under certain conditions of storage or use.

Section 11. Toxicological Information

Information on Toxicological Effects

Acute Toxicity	: No specific data available.
Irritation/Corrosion	: Product causes skin irritation and serious eye irritation.

Tantalum, tetraethoxy(hydrogen acetoacetato)-,ester

Safety Data Sheet

Section 11. Toxicological Information

Sensitization	: No specific data available.
Germ Cell Mutagenicity	: No effects known.
Carcinogenicity	
IARC	: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by ACGIH.
NTP	: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by NTP.
OSHA	: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by OSHA.
Reproductive Toxicity	: This product is not expected to cause reproductive or developmental effects.
Teratogenicity	: No specific data available.
Specific Target Organ Toxicity (Single Exposure)	: Respiratory tract irritation.
Specific Target Organ Toxicity (Repeated Exposure)	: No specific data available.
Aspiration Hazard	: No specific data available.
Information on the Likely Routes of Exposure	: Common routes of exposure: inhalation (failure to prevent dust formation), dermal (failure to use skin protection), eye (failure to use safety eyewear). Less common: ingestion (failure to employ recommended hygiene measures (e.g. smoking after handling product without washing hands or using hand protection)).
Additional Information	: Product may be harmful if swallowed. To the best of our knowledge, the chemical, physical and toxicological properties of this product have not been thoroughly investigated.

Section 12. Ecological Information

Numerical Measures of Toxicity

Toxicity to Fish	: No specific data available.
Toxicity to Daphnia and Other Aquatic Invertebrates	: No specific data available.

Tantalum, tetraethoxy(hydrogen acetoacetato)-,ester

Safety Data Sheet

Section 12. Ecological Information

Toxicity to Algae	: No specific data available.
Persistence and Degradability	
Biodegradability	: No specific data available.
Bioaccumulative Potential	: No specific data available.
Mobility in Soil	: No specific data available.
Other Adverse Effects	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13. Disposal Considerations

Waste Treatment Methods

Product	Dispose of in accordance with local, state, and federal regulations. Refer to 40 CFR 260-299 for complete waste disposal regulations. Consult your local, state, or federal agency before disposing of any chemicals.
Contaminated Packaging	Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Dispose of as unused product. DO NOT EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Section 14. Transport Information

	DOT	IMDG	IATA
UN Number	UN 1325	UN 1325	UN 1325
UN Proper Shipping Name	Flammable solids, organic, n.o.s (tantalum, tetraethoxy(hydrogen acetoacetato)-,ester)	FLAMMABLE SOLIDS, ORGANIC, N.O.S. (tantalum, tetraethoxy(hydrogen acetoacetato)-,ester)	Flammable solids, organic, n.o.s (tantalum, tetraethoxy(hydrogen acetoacetato)-,ester)
Transport Hazard Classes	4.1	4.1	4.1
Packing Group	II	II	II
Environmental Hazards	-	-	-
Additional Information	-	-	-

Special Precautions for User : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transporting in Bulk According to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

Tantalum, tetraethoxy(hydrogen acetoacetato)-,ester

Safety Data Sheet

Section 15. Regulatory Information

TSCA (Toxic Substance Control Act):

This product is not listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory). Use of this product is restricted to research and development only. This product must be used under the supervision of a technically qualified individual as defined by the TSCA. This product must not be used for commercial purposes or in formulations for commercial purposes.

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard (Flammable solid); Acute Health Hazard (Skin corrosion or irritation; Serious eye damage or eye irritation; Specific Target Organ Toxicity (STOT), single exposure: respiratory irritation).

Massachusetts Right to Know Components

No components are subject to Massachusetts Right to Know Act.

Pennsylvania Right to Know Components

No components are subject to Pennsylvania Right to Know Act.

New Jersey Right to Know Components

No components are subject to New Jersey Right to Know Act.

California Proposition 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Section 16. Other Information

National Fire Protection Association (U.S.A.)



Tantalum, tetraethoxy(hydrogen acetoacetato)-,ester

Safety Data Sheet

Section 16. Other Information

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

HMIS Rating

HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	1

History

Date of Printing : 6/3/2020

Date of Issue/Date of Revision : 6/3/2020

Date of Previous Issue : None.

References : None available.

Abbreviations and Acronyms

ACGIH: American Conference of Governmental Industrial Hygienists.

ATE: Acute Toxicity Estimate

CAS: Chemical Abstracts Service (division of the American Chemical Society).

DOT: US Department of Transportation.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

HMIS: Hazardous Materials Identification System.

HNOC: Hazards Not Otherwise Classified.

IARC: International Agency for Research on Cancer.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA).

IDLH: Immediately Dangerous to Life or Health (US National Institute for Occupation Health and Safety (NIOSH)).

IMDG: International Maritime Code for Dangerous Goods.

NFPA: National Fire Protection Association.

NIOSH: National Institute of Occupational Safety and Health.

NTP: National Toxicology Program.

OSHA: Occupational Safety and Health Administration.

PEL: Permissible Exposure Limits.

REL: Recommended Exposure Limits.

SARA: Superfund Amendments and Reauthorization Act.

STOT: Specific Target Organ Toxicity.

Tantalum, tetraethoxy(hydrogen acetoacetato)-,ester

Safety Data Sheet

Section 16. Other Information

Abbreviations and Acronyms (cont.)

TLV: Threshold Limit Values (ACGIH).

TWA: Time Weighted Average.

VOC: Volatile Organic Compound.

Disclaimer

The information herein is believed to be accurate and is presented in good faith; however, no warranties or representations are made by Ereztech LLC regarding the accuracy or completeness of the information. Ereztech LLC shall not be liable for any damages resulting from the handling, or from the contact with the above product.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

