

11555 Medlock Bridge Road, Suite 100, Johns Creek, GA 30097, USA

T: +1.888.658.1221 F: 1.678.619.2020

E: info@ereztech.com W: https://ereztech.com

SAFETY DATA SHEET

Section 1. Identification

<u>Tetraethoxytantalum acetylacetonate</u> **Product Name:**

Product Type: Solid

20219-33-4 **CAS Number: Product Number:** TA9334

Recommended Use: Laboratory chemicals, synthesis of substances.

This product is being supplied under the TSCA R&D Exemption (40 **Uses Advised Against:**

> CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless

appropriate consent is granted in writing by Ereztech LLC.

Ereztech LLC **Product Manufacturer:**

11555 Medlock Bridge Road, Suite 100

Johns Creek, GA 30097

Product Information: (888) 658-1221

CHEMTREC: 1-800-424-9300 (USA); In Case of an Emergency:

> +1 703-527-3887 (International); CCN836180 *** Contact manufacturer for all non-emergency calls.

Section 2. Hazards Identification

Appearance/Odor: Yellow crystals/crystalline powder, alcohol-like odor.

Classification: FLAMMABLE SOLIDS - Category 1, H228

SKIN CORROSION/IRRITATION – Category 2, H315

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A, H319 SPECIFIC ORGAN TOXICITY, SINGLE EXPOSURE; RESPIRATORY

TRACT IRRITATION - Category 3, H335

GHS Label Elements

Hazard Pictograms:



Signal Word: DANGER

Ereztech TA9334 Page 1 of 15 Revision: 1.10

Section 2. Hazards Identification

H228: Flammable solid. **Hazard Statements:**

H315: Causes skin irritation.

H319: Causes serious eye irritation. H335: May cause respiratory irritation.

Precautionary Statements

Response:

Prevention: P210: Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P240: Ground and bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting/processing

equipment.

P261: Avoid breathing dusts, aerosols, vapors and gases.

P264 + P265: Wash hands and exposed skin thoroughly after

handling. Do not touch eyes.

P271: Use only outdoors or with adequate ventilation.

P280: Wear protective gloves/ protective clothing/ eye protection/

face protection/hearing protection.

P302 + P352: IF ON SKIN: Wash with plenty of water.

P304 + P340: IF INHALED: Remove person to fresh air and keep

comfortable for breathing.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P319: Get medical help if you feel unwell.

P332 + P317: If skin irritation occurs: Get medical help.

P337 + P317: If eye irritation persists: Get medical help.

P362 + P364: Take off contaminated clothing and wash it before

reuse.

P370 + P378: In case of fire: Use dry chemical or carbon dioxide

to extinguish.

P403 + P233: Store in a well ventilated place. Keep container Storage:

tightly closed.

P405: Store locked up.

P501: Dispose of contents/container in accordance with federal, Disposal:

state and local regulations.

This material is considered hazardous by the OSHA Hazard **OSHA/HCS Status:**

Communication Standard (29 CFR 1910.1200).

Hazards Not Otherwise

Classified (HNOC):

Reacts with water and moisture in air to release ethanol.

Section 3. Composition/Information on Ingredients

Mono-constituent. **Substance Type:**

Ereztech TA9334 Page 2 of 15 Revision: 1.10

Section 3. Composition/Information on Ingredients

Synonyms: Tantalum(V) tetraethoxyacetylacetonate; tantalum

tetraethoxy acetylacetonate; tantalum(V) tetraethoxide 2,4-

pentanedionate.

Formula: $C_{13}H_{27}O_6Ta$ Molecular Weight: 460.30 g/mol. 681-055-3

Component Name	%	CAS Number
<u>Tetraethoxytantalum acetylacetonate</u>	≥ 99	20219-33-4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

Section 4. First Aid Measures

Description of Necessary First Aid Measures

General Advice: Move out of dangerous area. If unconscious, place in recovery position and get

medical help immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Show this safety data sheet to the doctor in

attendance.

Eye Contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and

lower eyelids. Check for and remove any contact lenses if easy to do. Continue

rinsing. Get medical help if eye irritation develops and persists.

Skin Contact: Take off contaminated clothing and shoes immediately. Wash off contaminated

skin with plenty of water. Get medical help if irritation develops and persists.

Inhalation: Remove person to fresh air and keep comfortable for breathing. If not

breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person

providing aid to give mouth-to-mouth resuscitation. Get medical help if

symptoms develop or if you feel unwell.

Ingestion: Rinse mouth. Do NOT induce vomiting. Remove dentures if any. If vomiting

occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Get medical help if

symptoms develop or if you feel unwell.

Most Important Symptoms/Effects, Acute and Delayed Potential Acute Health Effects

Eye Contact: Symptoms may include stinging, tearing, redness, swelling and blurred vision.

Skin Contact: Symptoms may include an itching or burning sensation, reddening, swelling and

blistering with tissue necrosis.

Inhalation: Product may be irritating to respiratory system. Symptoms may include

coughing, sneezing with phlegm production, sore throat, nausea, headache, vomiting, dizziness, drowsiness, impairment of coordination and reaction time.

Ereztech TA9334 Page 3 of 15 Revision: 1.10

Section 4. First Aid Measures

Ingestion: Product may be harmful if swallowed and may be expected to be irritating to

mucous membranes. Symptoms may include cramping, localized pain,

headache, nausea, vomiting, dizziness, drowsiness, impairment of coordination

and reaction time.

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary

Notes to Physician: Treat symptomatically.

Specific Treatments: No specific treatment.

Protection of First Responders: No action taken shall be taken involving any personal risk

without suitable training. It may be dangerous to the person

providing aid to give mouth-to-mouth resuscitation.

See Toxicological Information (Section 11)

Section 5. Fire Fighting Measures

General Hazards: Flammable solid. Product reacts slowly with water and

moisture in air to release ethanol.

Suitable Extinguishing Media: THE MOST EFFECTIVE FIRE EXTINGUISHING AGENT IS DRY

CHEMICAL POWDER PRESSURIZED WITH NITROGEN.

Carbon dioxide (CO2) may also be used.

Unsuitable Extinguishing Media: Do not use water jet as an extinguisher as it may scatter and

spread the fire.

Unusual Fire and Product reacts slowly with water and protic solvents to release ethanol. Vapor/air mixtures are explosive above flash point.

ethanol. Vapor/air mixtures are explosive above flash point. Product runoff to sewer may create a fire or explosion hazard. Vapors/gases released under fire conditions are heavier than air and may spread long distances along the ground. Vapors

may accumulate in low or confined areas or travel a

considerable distance to an ignition source and flashback.

Product of Combustion: Carbon oxides (CO_x) and tantalum oxides. Irritating fumes

and organic acid vapors may be generated during exposure to

elevated temperatures or open flame.

Protection of Firefighters: Promptly isolate the scene by removing all persons from the

vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Avoid contact with skin or eyes. Avoid the formation and inhalation of dusts, aerosols, vapors and gases.

Eliminate all local and distant ignition sources. Move containers from fire area if process can be accomplished

without risk to firefighters.

Section 5. Fire Fighting Measures

Protection of Firefighters (cont.):

To reduce the possibility of explosion, use a water spray or fog to reduce direct vapors and to cool unopened containers. Do not apply water directly to product. Do not cut, grind, drill or weld on or near product containers (even empty) of this product because an explosion may result.

Fire-fighters should wear appropriate protection equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

Section 6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel:

No action shall be taken involving any personal risk or without suitable training. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Take action to prevent static discharges. Use non-sparking tools and equipment. Beware of vapors accumulating in low areas to form explosive concentrations. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Prevent contact with skin, eyes or clothing. Prevent the formation and inhalation of dusts, aerosols, vapors and gases. Provide adequate ventilation or wear respiratory protection.

For Emergency Responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For Non-Emergency Personnel".

Environmental Precautions:

Prevent spilled material and firefighting runoff from entering the surrounding environment (soil contact, entry into drains, sewers and waterways). Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for Containment General:

Eliminate all local and distant ignition sources – NO SMOKING. Stop spillage and move containers from spill area if safe to do so. Avoid the formation and inhalation of dusts, aerosols, vapors and gases. Use spark-proof tools and explosion-proof equipment. Dispose of collected spillage in accordance with federal, state and local regulations.

Ereztech TA9334 Page 5 of 15 Revision: 1.10

Section 6. Accidental Release Measures

General (cont.): Contaminated binding material may pose the same hazard as

the spilled product.

Small Spill: Collect spillage with a dry, non-combustible binding material

(e.g. dry sand, vermiculite or diatomaceous earth) and place in

dry, sealed container for disposal.

Large Spill: Approach release from upwind. Prevent entry into sewers,

water courses, basements or confined areas. Contain and collect spillage with a dry, non-combustible binding material (e.g. dry sand, vermiculite or diatomaceous earth) and place in

dry, sealed container for disposal.

Note: see Section 1 for emergency contact information and

Section 13 for waste disposal.

Section 7. Handling and Storage

Precautions:

Product reacts slowly with water to release ethanol; handle under a dry, inert gas. Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Keep away from all sources of ignition – NO SMOKING. Keep container tightly sealed. Avoid contact with skin, eyes and clothing. Avoid the formation and inhalation of dusts, aerosols, vapors and gases. Do not ingest. Avoid prolonged exposure. Ensure adequate ventilation or wear respiratory protection.

Protective Measures:

Protect against electrostatic discharges. Use explosion-proof electrical/ventilating/lighting/handling equipment. Use non-sparking tools and equipment. Put on appropriate personal protective equipment (see Section 8). Keep in the original container kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

General Occupational Hygiene:

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Safe Storage Conditions:

Product reacts slowly with water to release ethanol; store under an inert gas. Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Keep away from all

sources of ignition – NO SMOKING.

Section 7. Handling and Storage

Safe Storage Conditions (cont.):

Store in original container protected from direct sunlight in a dry and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Store locked up.

Section 8. Exposure Controls/Personal Protection

Introductory Remarks:

These recommendations provide general guidance for handling this product. Because work environments and material handling practices vary, safety procedures should be developed for each intended application. While developing safe handling procedures, do not overlook the need to clean equipment and conduct regular repairs. Waste from these procedures should be handled in accordance with Section 13.

Occupational Exposure Limits

Components	CAS-No.	List	Туре	Value
Ethanol	64-17-5	ACGIH	TLV	1000 ppm STEL
		NIOSH	REL	1000 ppm TWA
			1	1900 mg/m ³ TWA 3300 ppm IDLH
		OSHA	PEL	1000 ppm TWA
				1900 mg/m ³ TWA

Engineering Controls:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute. Provide an eyewash/shower station.

Environmental Exposure Controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual Protection Measures

Hygiene Measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Remove all soiled and contaminated clothing immediately. Do not inhale dusts, aerosols, vapors or gases. Avoid contact with eyes and skin. Ensure that eyewash stations and safety showers are close to the workstation location.

Ereztech TA9334 Page 7 of 15 Revision: 1.10

Section 8. Exposure Controls/Personal Protection

Eye/Face Protection:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to dusts and aerosols. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles, faceshield (8-inch minimum). Refer to 29 CFR 1910.133, ANSI Z87.1, or European Standard EN166.

Skin Protection

Hand Protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Chemical-resistant gloves.

Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. For full contact, wear Neoprene or nitrile rubber gloves.

Other Skin Protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity discharges, wear anti-static, flame retardant protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Respiratory Protection:

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Section 9. Physical and Chemical Properties

Physical State: Solid (crystals/crystalline powder).

Ereztech TA9334 Page 8 of 15 Revision: 1.10

Section 9. Physical and Chemical Properties

Color: Yellow.

Odor: Alcohol-like (ethanol).

Odor Threshold: No data available.

Melting Point: 45 °C (113 °F).

Boiling Point: 95 °C (203 °F). **Flash Point:** Not applicable.

Flammability (solid, gas): Product is a category 1 flammable solid.

Density: 1.5 g/cm³ @ 20 °C (68 °F).

Vapor Pressure: No data available.

Relative Vapor Density: >1.

Water Solubility: Insoluble, reacts exothermally with water to release

ethanol.

Evaporation Rate: Not applicable. Viscosity: Not applicable.

Section 10. Stability and Reactivity

Reactivity: Product reacts slowly with water and protic solvents to release ethanol.

Chemical Stability: This product is stable when stored under a dry, inert

atmosphere and away from heat. Nitrogen containing less than 5 ppm each moisture and air is recommended.

Conditions to Avoid: Exposure to water/moisture, sources of ignition (heat,

flames, sparks, electrostatic discharges), extremes of

temperature and direct sunlight.

Incompatible Materials: Strong oxidizing agents.

Hazardous Decomposition Products: Hazardous decomposition products formed under fire

conditions: ethanol, carbon oxides (CO_X) and tantalum oxides. Irritating fumes and organic acid vapors may be generated during exposure to elevated temperatures or

open flame. In the event of a fire: see Section 5.

Possibility of Hazardous Reactions: Under normal conditions of storage and use noted above,

hazardous reactions will not occur. Hazardous reactions or instability may occur under certain conditions of storage or use. Product reacts slowly with water to

release ethanol.

Section 11. Toxicological Information

Information on Toxicological Effects

No specific data available. May be harmful if ingested or **Acute Toxicity:**

inhaled

Irritation/Corrosion: Product causes skin irritation and serious eye irritation.

Sensitization: No specific data available. No specific data available. Germ Cell Mutagenicity:

Carcinogenicity

Component	CAS No	ACGIH	IARC	NTP	OSHA
Ethanol	64-17-5	A3 (Animal carcinogen)	Known carcinogen	Not listed	Not listed

Reproductive Toxicity: No specific data available.

No specific data available. **Teratogenicity:**

Specific Target Organ Toxicity: Respiratory tract irritation. (Single Exposure)

No specific data available. **Specific Target Organ Toxicity:**

(Repeated Exposure)

No specific data available. **Aspiration Hazard:**

Information on the Likely Common routes of exposure: inhalation (failure to prevent dust formation), dermal (failure to use skin **Routes of Exposure:** protection), eye (failure to use safety eyewear). Less common: ingestion (failure to employ recommended hygiene measures (e.g. smoking after handling product

without washing hands or using hand protection).

Product may be harmful if ingested or inhaled. Prolonged **Additional Information:** exposure to ethanol vapors released by product hydrolysis may be harmful to nervous system and liver. Product has an irritating, dehydrating effect on overexposed tissues due to ethanol released during hydrolysis of product.

> To the best of our knowledge, the chemical, physical and toxicological properties of this product have not been thoroughly investigated.

Section 12. Ecological Information

Ecotoxicity: The impact of this product on the environment has not

been tested.

Numerical Measures of Toxicity: No specific data available.

Ereztech TA9334 Page 10 of 15 Revision: 1.10

Section 12. Ecological Information

Persistence and Degradability

Biodegradability: No specific data available.

Bioaccumulative Potential: No specific data available.

Mobility in Soil: No specific data available.

Results of PBT and vPvB Assessment: PBT/vPvB assessment not available as chemical safety

assessment not required/not conducted.

Endocrine Disrupting Properties: No specific data available.

Other Adverse Effects:

An environmental hazard cannot be excluded in the

event of unprofessional handling or disposal.

Section 13. Disposal Considerations

Waste Treatment Methods

Product:

Contaminated Packaging:

Dispose of in accordance with local, state, and federal regulations. Refer to 40 CFR 260-299 for complete waste disposal regulations. Consult your local, state, or federal agency before disposing of any chemicals. Empty containers retain product residue (dusts, aerosols, vapors, and gases) and can be dangerous. Dispose of as unused product. DO NOT EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Section 14. Transport Information

	DOT	IMDG	IATA
UN Number	UN1325	UN1325	UN1325
UN Proper Shipping Name	Flammable solids, organic, n.o.s (Tetraethoxy- tantalum acetylacetonate)	FLAMMABLE SOLIDS, ORGANIC, N.O.S. (Tetraethoxy- tantalum acetylacetonate)	Flammable solids, organic, n.o.s (Tetraethoxy- tantalum acetylacetonate)
Transport Hazard Classes	4.1	4.1	4.1
Packing Group	П	П	П
Environmental Hazards	-	-	-
Additional Information	-	EMS-No: F-A, S-G	-

Ereztech TA9334 Page 11 of 15 Revision: 1.10

Section 14. Transport Information

Special Precautions for User:

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory Information

Toxic Substance Control Act (TSCA)

This product is not listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory). Use of this product is restricted to research and development only. This product must be used under the supervision of a technically qualified individual as defined by the TSCA. This product must not be used for commercial purposes or in formulations for commercial purposes.

This product as supplied is not subject to the TSCA Significant New Use Rule.

This product as supplied is not subject to TSCA 12(b) export notification requirements.

SARA 302 Components

This product does not contain any components which are subject to the reporting requirements of SARA Title III, Section 302 EHS TPQ.

SARA 304 Components

This product does not contain any components which are subject to the reporting requirements of SARA Title III, Section 304 RQ.

SARA 311/312 Hazards

Fire Hazard (Flammable solid); Acute Health Hazard (Skin corrosion or irritation; Serious eye damage or eye irritation; Specific Target Organ Toxicity (STOT), single exposure: respiratory irritation).

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

Not applicable.

Clean Air Act

Not applicable.

CERCLA Reportable Quantity

This product, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US Department of Homeland Security (DHS)

This product does not contain any DHS chemicals.

Section 15. Regulatory Information

US Department of Transportation (DOT)

Component	Reportable Quantity	DOT Marine Pollutant	DOT Severe Marine Pollutant
Tetraethoxytantalum acetylacetonate	No	No	No

US State Right-to-Know Listings

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Tetraethoxytantalum acetylacetonate	-	-	-	-	-

[&]quot;X" - Listed.

US State Chemicals of High Concern Listings

Component	Maine	Vermont	Washington
Tetraethoxytantalum acetylacetonate	-	- 4	-

[&]quot;X" - Listed.

California Proposition 65 Components

This product does not contain any Proposition 65 chemicals.

Section 16. Other Information

National Fire Protection Association



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety. Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only.

Ereztech TA9334 Page 13 of 15 Revision: 1.10

Section 16. Other Information

National Fire Protection Association (cont.)

Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

HMIS Rating

HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	1

History

Date of Issue/Date of Revision: 10/27/2025. 11/18/2022. **Date of Previous Issue:** References: None available.

Abbreviations and Acronyms

ACGIH : American Conference of Governmental Industrial Hygienists.

AIHA : American Industrial Hygiene Association.

: Acute Toxicity Estimate (per Chapter 3.1 of GHS 11 standard). ATF

Biological Exposure Indices (ACGIH). BEI

: Chemical Abstracts Service (division of the American Chemical Society). CAS

: Chemical Hazards Response Information System (US DOT). CHRIS CLP : Classification, Labeling and Packaging (European Union (EU)).

DOT US Department of Transportation.

EC-No. : The EC Inventory (EINECS, ELINCS and the NLP-list is the source of the seven digit

EC number, an identifier of substances commercially available with the EU (European

Union).

European Inventory of Existing Commercial Chemical Substances. **EINECS**

Extremely Hazardous Substance. **EHS**

ELINCS European List of Notified Chemical Substances.

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

HAP Hazardous Air Pollutants (Clean Air Act). Hazardous Materials Identification System. HMIS

HNOC : Hazards Not Otherwise Classified.

IARC : International Agency for Research on Cancer.

IATA International Air Transport Association.

IATA-DGR Dangerous Goods Regulations by the "International Air Transport Association"

(IATA).

: Immediately Dangerous to Life or Health (US National Institute for Occupation Health **IDLH**

and Safety (NIOSH)).

International Maritime Code for Dangerous Goods. **IMDG**

IΡ Intraperitoneal. IV : Intravenous.

NFPA : National Fire Protection Association.

NIOSH : National Institute of Occupational Safety and Health.

Section 16. Other Information

Abbreviations and Acronyms (cont.)

NSRL : No Significant Risk Levels. NTP : National Toxicology Program.

ODS : Ozone Depleting Substances (US Clean Air Act).

OECD : Organization for Economic Co-Operation and Development.

OEL : Occupational Exposure Limit.

OSHA : Occupational Safety and Health Administration.

PBT : Persistent Bioaccumulative and Toxic.

PEL : Permissible Exposure Limits.
REL : Recommended Exposure Limits.

RQ : Reportable Quantity.

SARA : Superfund Amendments and Reauthorization Act.

STEL (ST) : Short Term Exposure Limit (ACGIH/NIOSH)

STOT : Specific Target Organ Toxicity.
 TLV : Threshold Limit Values (ACGIH).
 TPQ : Threshold Planning Quantity.
 TWA : Time Weighted Average.
 VOC : Volatile Organic Compound.

vPvB : Very Persistent and Very Bioaccumulative.

WEEL : Workplace Environmental Exposure Level (AIHA).

Disclaimer

The information herein is believed to be accurate and is presented in good faith; however, no warranties or representations are made by Ereztech LLC regarding the accuracy or completeness of the information. Ereztech LLC shall not be liable for any damages resulting from the handling, or from the contact with the above product.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.